THIS DOCUMENT AND ATTACHMENT(S) ARE AVAILABLE FOR DOWNLOAD AT

http://www.bxwa.com/bxwa_toc/pub/1687/toc.html

AN EMAIL NOTIFICATION WAS SENT TO REGISTERED PLANHOLDERS. FAILURE TO ACKNOWLEDGE RECEIPT ON THE BID FORM DOES NOT AFFECT THE BIDDER'S OBLIGATION FOR COMPLIANCE.



ADDENDUM NO. 2

WASHINGTON STATE PARKS AND RECREATION COMMISSION NORTHWEST REGION HEADQUARTERS NW REGION HQ REMODEL NW-C35NW

DATE: January 02, 2025

ATTENTION TO PLANHOLDERS OF RECORD. This Addendum supersedes and supplements all portions of the Bid Set Invitation to Bid and specifications for the solicitation posted on November 20, 2024, with which it concerns. The Addendum becomes part of the Contract Documents upon issuance. Receipt of the addendum must be acknowledged on bid for bid to be considered valid.

This Addendum includes the following Sections and Attachments:

Section 1: Bidder Questions Section 2: Attachments

SECTION 1: BIDDER QUESTIONS

QUESTIONS:

1. There are no Data Specs Division 27? Will owner provide specification or take care of data installation in house?

Answer: Contractor provides pathway for cabling. Cat6 Cabling by Washington State Park under separate contract. All cables will be terminated on RJ45 keystone jacks. Jack will need to be wired for T568B.

2. There is no door or frame specification in Div 8. Will this be provided by addendum?

Answer:

- a. Exterior doors basis of design is Kawneer 451UT per spec.
- b. Wood doors are specified in Section 081416. Interior doors are called out on door schedule as wood frames, with detail at 4/sheet 21, with painted wood trim and frames. Wood doors to be solid core five-ply structural composite lumber cores, factory primed, painted.
- c. (Specification 081416 attached)

SECTION 2: ATTACHMENTS

Specification Section 081416 (1 page)

Brett Taylor	02 January, 2025
Brett Taylor, Procurement Coordinator	Date
Contracts and Grants Program	

END OF ADDENDUM NO. 2

NW Region HQ Remodel

SECTION 081416 FLUSH WOOD DOORS FLUSH WOOD DOORS

PART 1 GENERAL

1.01 SECTION REQUIREMENTS

- A. Submittals: Product Data; Shop Drawings, Door Schedule, Samples for each face material and finish.
- B. Quality Standard: In addition to requirements specified, comply with WDMA I.S.1-A, "Architectural Wood Flush Doors."
- Field Measurements: Verify actual measurements/openings by field measurements before fabrication.

PART 2 PRODUCTS

2.01 FLUSH WOOD DOORS

- A. Doors for Opaque Finish: Custom grade
 - Faces: Medium-density overlay.
- B. Door Construction:
 - 1. Interior Solid-Core Doors: Five-ply, structural composite lumber cores.

2.02 FABRICATION AND FINISHING

- A. Factory fit doors to suit frame-opening sizes indicated and to comply with referenced quality standard wherever practical.
- B. Factory machine doors for hardware that is not surface applied.
- C. Cut and trim openings to comply with referenced standards.
 - 1. Trim light openings with moldings indicated.
 - 2. Factory install louvers in prepared openings.
- D. Factory-prime doors scheduled to receive field finish painting.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Comply with WDMA's "How to Store, Handle, Finish, Install, and Maintain Wood Doors."
 - 1. Install doors to comply with manufacturer's written instructions and the referenced quality standard, and as indicated.
 - 2. Install fire-rated doors to comply with NFPA 80.
- B. Align doors in frames with uniform clearances and bevels. Where not factory fitted and machined, fit doors for frames and machine doors for hardware; seal cut surfaces after fitting and machining.
- Repair, refinish, or replace factory-finished doors damaged during installation, as directed by Architect.

END OF SECTION